


## CF Tee



- One fixed and two rotatable (one on each axis) flanges
- Pressure range:  $1 \cdot 10^{-12}$  mbar to ambient pressure
- Custom lengths available upon request
- Tube surface: Glass bead blasted (polished version on request)
- Tightness:  $\leq 1 \cdot 10^{-10}$  mbar l/s
- Bake out range is up to 450°C

### Dimensions



#### Stainless Steel 304/1.4301

- Temperature range: -196 to 300 °C
- Flange material: SS304 / 1.4301
- Tube material: SS304 / 1.4301

| Flange Size (DN) | A (mm) | B (mm) | Order No         |
|------------------|--------|--------|------------------|
| 16               | 76     | 38     | VC4FTB1SS016-76  |
| 40               | 126    | 63     | VC4FTB1SS040-126 |
| 63               | 210    | 105    | VC4FTB1SS063-210 |
| 100              | 270    | 135    | VC4FTB1SS100-270 |
| 160              | 334    | 167    | VC4FTB1SS160-334 |

#### Stainless Steel 316L/1.4404

- Temperature range: -196 to 350 °C
- Flange material: SS316L / 1.4404
- Tube material: SS316L / 1.4404

| Flange Size (DN) | A (mm) | B (mm) | Order No         |
|------------------|--------|--------|------------------|
| 16               | 76     | 38     | VC4FTB2SS016-76  |
| 40               | 126    | 63     | VC4FTB2SS040-126 |
| 63               | 210    | 105    | VC4FTB2SS063-210 |
| 100              | 270    | 135    | VC4FTB2SS100-270 |
| 160              | 334    | 167    | VC4FTB2SS160-334 |